



## DESCRIPTION

- Weight transmitter with 4 independent reading channels with display of the total weight.
- The TLB4 series allows to have same benefits and performance of an advanced digital weighing system even using analog load cells.
- Back panel mounting on Omega/DIN rail (space-saving vertical shape).
- Front panel mounting (except PROFIBUS DP version) with fixing kit included (panel drilling template: 96x23 mm; panel thickness: 2.5 mm).
- Dimensions: 115x26x120 mm.
- 6-digit semi-alphanumeric red LED display (8 mm height).
- 6 signalling LED.
- Four buttons for the system calibration.
- IP30 front panel protection rating.
- Removable screw terminal blocks.
- The instrument can be configured and managed using the free "Instrument Manager" PC software, which you can download from [www.laumas.com](http://www.laumas.com).

Front panel mounting (fixing kit included)



## INPUTS/OUTPUTS AND COMMUNICATION

- RS485 serial port for communication via protocols ModBus RTU, ASCII Laumas or continuous one way transmission.
- 3 relay outputs controlled by the setpoint values or via protocols.
- 2 optoisolated PNP digital inputs: status reading via serial communication protocols.
- 4 load cell dedicated inputs.

## CERTIFICATIONS

|                           |  |
|---------------------------|--|
|                           | OIML R76:2006, class III, 3x10000 divisions, 0.25 µV/VSI / OIML R61, R51 - WELMEC Guide 8.8:2017 (MID) |
|                           | UL Recognized component - Complies with United States and Canada regulations                           |
|                           | Complies with the Eurasian Customs Union regulations   |
|                           | Equivalent of the CE marking for the United Kingdom  |
|                           | NMI Trade Approved - Complies with Australian market regulations for legal for trade use               |
|                           | Complies with New Zealand regulations for legal for trade use  |
|                           | Complies with United Kingdom regulations for legal for trade use                                       |
|                           | Complies with the Brazilian regulations for legal for trade use  |
| CERTIFICATIONS ON REQUEST |  |
|                           | Conformity assessment (initial verification) in combination with Laumas weighing module (CE - UKCA)    |

## FIELDBUSES



## WEIGHT TRANSMITTER - 4 INDEPENDENT CHANNELS

| DESCRIPTION   | CODE           |
|---|----------------|
|  <b>RS485</b> serial port.<br>Baud rate: 2400, 4800, 9600, 19200, 38400, 115200 (bit/s).   | TLB4RS485      |
|  Optoisolated 16 bit <b>analog output</b> .<br>Current: 0÷20 mA; 4÷20 mA (up to 300 Ω).<br>Voltage: 0÷10 V; 0÷5 V; ±10 V; ±5 V (min 10 kΩ).<br>Equipped with RS485 serial port.                                      | TLB4           |
|  <b>CANopen</b> port.<br>Baud rate: 10, 20, 25, 50, 100, 125, 250, 500, 800, 1000 (kbit/s).<br>The instrument works as <i>slave</i> in a synchronous CANopen network.<br>Equipped with RS485 serial port.            | TLB4CANOPEN    |
|  <b>DeviceNet</b> port.<br>Baud rate: 125, 250, 500 (kbit/s).<br>The instrument works as <i>slave</i> in a DeviceNet network.<br>Equipped with RS485 serial port.  | TLB4DEVICENET  |
|  <b>CC-Link</b> port.<br>Baud rate: 156, 625, 2500, 5000, 10000 (kbit/s).<br>The instrument works as <i>Remote Device Station</i> in a CC-Link network and occupies 3 stations.<br>Equipped with RS485 serial port.  | TLB4CCLINK     |
|  <b>Profibus DP</b> port.<br>Baud rate: up to 12 Mbit/s.<br>The instrument works as <i>slave</i> in a Profibus DP network.<br>Equipped with RS485 serial port.  | TLB4PROFIBUS   |
|  <b>Modbus/TCP</b> port.<br>Type: RJ45 10Base-T or 100Base-TX (auto-sensing).<br>The instrument works as <i>slave</i> in a Modbus/TCP network.<br>Equipped with RS485 serial port.                                 | TLB4MODBUSTCP  |
|  <b>Ethernet TCP/IP</b> port.<br>Type: RJ45 10Base-T or 100Base-TX (auto-sensing).<br>The instrument works in an Ethernet TCP/IP network and it is accessible via web browser.<br>Equipped with RS485 serial port. | TLB4ETHETCP    |
|  <b>2x Ethernet/IP</b> ports.<br>Type: RJ45 10Base-T or 100Base-TX (auto-sensing).<br>The instrument works as <i>adapter</i> in an Ethernet/IP network.<br>Equipped with RS485 serial port.                        | TLB4ETHEIP     |
|  <b>2x Profinet IO</b> ports.<br>Type: RJ45 100Base-TX.<br>The instrument works as <i>device</i> in a Profinet IO network.<br>Equipped with RS485 serial port.   | TLB4PROFINETIO |
|  <b>2x EtherCAT</b> ports.<br>Type: RJ45 10Base-T or 100Base-TX (auto-sensing).<br>The instrument works as <i>slave</i> in an EtherCAT network.<br>Equipped with RS485 serial port.                                | TLB4ETHERCAT   |
|  <b>2x POWERLINK</b> ports.<br>Type: RJ45 10Base-T or 100Base-TX (auto-sensing).<br>The instrument works as <i>slave</i> in a Powerlink network.<br>Equipped with RS485 serial port.                               | TLB4POWERLINK  |
|  <b>2x SERCOS III</b> ports.<br>Type: RJ45 10Base-T or 100Base-TX (auto-sensing).<br>The instrument works as <i>slave</i> in a Sercos III network.<br>Equipped with RS485 serial port.                             | TLB4SERCOS     |

## WEIGHT TRANSMITTER - 4 INDEPENDENT CHANNELS

## TECHNICAL FEATURES

|  |   |
|--|---|
| Power supply and consumption                                     | 12÷24 VDC ±10%; 5 W   |
| Number of load cells • Load cells supply                         | up to 16 (350 Ω) - 4/6 wires • 5 VDC/240 mA   |
| Linearity • Analog output linearity (only for TLB4)              | <0.01% full scale • <0.01% full scale   |
| Thermal drift • Analog output thermal drift (only for TLB4)      | <0.0005% full scale/°C • <0.003% full scale/°C  |
| A/D Converter  | 4 channels - 24 bit (16000000 points) - 4.8 kHz   |
| Divisions (with measurement range ±10 mV and sensitivity 2 mV/V) | ±999999 • 0.01 µV/d   |
| Measurement range  | ±39 mV  |
| Usable load cells sensitivity                                    | ±7 mV/V   |
| Conversions per second   | 600   |
| Display range  | ±999999   |
| Decimals • Display increments                                    | 0÷4 • x1 x2 x5 x10 x20 x50 x100   |
| Digital filter • Readings per second                             | 21 levels • 5÷600   |
| Relay outputs  | 3 - max 115 VAC/150 mA  |
| Optoisolated digital inputs                                      | 2 - 5÷24 VDC PNP  |
| Serial ports   | RS485   |
| Baud rate  | 1200, 2400, 4800, 9600, 19200, 38400, 115200 (bit/s)  |
| Optoisolated analog output (only for TLB4)                       | 16 bit = 65535 divisions. 0÷20 mA; 4÷20 mA (up to 300 Ω)<br>0÷10 V; ±5 V; ±10 V; ±5 V (min 10 kΩ) |
| Humidity (condensate free)                                       | 85%   |
| Storage temperature  | -30 °C +80 °C   |
| Working temperature  | -20 °C +60 °C   |

|   |                     |                               |
|---|---------------------|-------------------------------|
|  | Relay outputs       | 3 - max 30 VAC, 60 VDC/150 mA |
|   | Working temperature | -20 °C +60 °C                 |
| Equipment to be powered by 12-24 VDC LPS or Class 2 power source                    |                     |                               |

METROLOGICAL SPECIFICATIONS  
OF TYPE-APPROVED INSTRUMENTS

|  | OIML  | INMETRO  |
|--|---|--|
| Applied standards by region                          | EU: 2014/31/UE - EN45501:2015 - OIML R76:2006<br>Australia: National Measurement Regulations 1999<br>New Zealand: Weights and Measures Regulations 1999<br>United Kingdom: Non-automatic Weighing Instrument Regulations 2016 | Brazil: Portaria Inmetro N°157/2022                |
| Operation modes                                      | single interval, multi-interval<br>multiple range   | single interval, multi-interval,<br>multiple range |
| Accuracy class                                       | III or IIII   | III  |
| Maximum number of scale verification divisions       | 10000 (class III); 1000 (class IIII)  | 10000 (class III)                                  |
| Minimum input signal for scale verification division | 0.25 µV/VSI   | 0.25 µV/VSI  |
| Working temperature                                  | -10 °C +40 °C   | -10 °C +40 °C                                      |

## OPTIONS ON REQUEST

|   | DESCRIPTION   | CODE      |
|---|---------------|-----------|
|  | Alibi memory. | OPZWALIBI |

## WEIGHT TRANSMITTER - 4 INDEPENDENT CHANNELS

## MAIN FUNCTIONS

- 4 independent channels for load cells: monitoring and direct management of each connected load cell.
- Immediate reporting of anomalies (also on the connected weight indicator display).
- TLB4 functions can be managed by a W series weight indicator connected via RS485 serial port (excluding instruments with graphic display) or remotely via the communication interfaces.
- Digital equalization of active channels for a single load cell or an axis.
- Load distribution analysis on the 4 channels with backups archive: storing, consultation, printing.
- Single channel overload function.
- Detailed diagnostics of each load cell (max 4): depending on the type of weighing system you can perform:
  - load automatic diagnostics;
  - automatic diagnostics on zero.
- Tilt compensation of the weighing system up to  $\pm 10$  degrees via inclinometer (not included). The weight correction is also valid for systems approved for legal for trade use.
- Archive of the last 50 significant events (zeroing, calibration, equalization, alarms): storing, consultation, printing.
- Transmission via RS485 (Modbus RTU) or fieldbus of the divisions for the 4 reading channels. Only the points of each load cell connected are transmitted, with no filter applied; the calculation of the weight value, the zero setting and calibration are made by the customer.
- Transmission of load distribution percentages via RS485 (Modbus RTU) or fieldbus.
- Connections to:
  - PLC via analog output or fieldbus;
  - PC/PLC via RS485 (up to 99 instruments with line repeaters, up to 32 without line repeaters);
  - remote display, inclinometer and printer via RS485;
  - up to 16 load cells in parallel;
  - W series weight indicator via RS485;
  - IoT gateway for cloud connection via RS485.

- TCP/IP WEB APP: integrated software in combination with the Ethernet TCP/IP version for remote supervision, management and control of the instrument.
- Digital filter to reduce the effects of weight oscillation.
- Possibility to define the condition of stable weight.
- Theoretical calibration (via keyboard) and real calibration (with sample weights and the possibility of weight linearization up to 8 points).
- Tare weight zero setting.
- Automatic zero setting at power-on.
- Gross weight zero tracking.
- Semi-automatic tare (net/gross weight) and preset tare.
- Semi-automatic zero.
- Direct connection between RS485 and RS232 without converter.
- Hysteresis and setpoint value setting.

## Approved versions for legal for trade use

- System parameters management protected by qualified access via software (password), hardware or fieldbus.
- Weight subdivisions displaying (1/10 e).
- Two operation mode: single interval or multi-interval.
- Net weight zero tracking.
- Calibration.
- Alibi memory (option on request).

## SINGLE PRODUCT LOADING PROGRAM


- Settable dosage formula.
- Automatic fall calculation.
- Tolerance error control.
- Precision batching through slow function.
- Precision batching through tapping function.
- Consumption storage.
- Printing of batching data.
- Alarm contact management.
- Batching start via external contact or fieldbus.
- Autotare at batching start.

## DIGITAL EQUALIZATION

The TLB4 does not require the use of the junction box thanks to the support of 4 independent channels; the digital equalization function simplifies the procedure to a single step and it is free of drift over time.


## CORNER mode

The sample weight is positioned in correspondence with each load cell



## AXIS mode

The sample weight is positioned in correspondence with the axes formed by the pairs of load cells



*The Company reserves the right to make changes to the technical data, drawings and images without notice.*